

IDLER SPROCKETS



Now available at UBC is the range of Bohma Power Transmission idler sprockets. Bohma idler sprockets feature **flame hardened teeth** and **black oxide coating** as standard giving long service life to your chain drive. Combine these with the wide range of shaft sizes available in UBC ball bearings to get more flexibility.

[See other side of brochure for stocked sizes.](#)



**Head Office
Sydney**

7 Toohey Road Wetherill Park NSW 2164
Phone: (02) 9756 2228 **Fax:** (02) 9756 2221
Email: sales@universalbearings.com.au

Victoria:

11/355-365 South Gippsland Highway Dandenong VIC 3175
Phone: (03) 9702 7668 **Fax:** (03) 9702 7828
Email: vicsales@universalbearings.com.au

Queensland:

Mobile: 0412 678 768
Email: dennis@universalbearings.com.au

www.universalbearings.com.au



Quality
Endorsed
Company
ISO 9001:2000
LIC QEC20818

STOCKED SIZES

BS SERIES				
SPROCKET PART #	SUITS CHAIN	TEETH / OD(mm)	BEARING SHAFT SIZES (mm)	BEARING SHAFT SIZES (inch)
IS-06A-15-35	06B—3/8	15T— 49.3	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-08A-15-35	08B— 1/2	15T— 65.5	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-08A-15-47	08B— 1/2	15T— 65.5	17, 20, 25	5/8, 3/4, 7/8, 1”
IS-10A-15-35	10B—5/8	15T— 83.0	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-12A-15-47	12B—3/4	15T— 99.8	17, 20, 25	5/8, 3/4, 7/8, 1”
IS-16A-13-47	16B—1”	13T— 117.0	17, 20, 25	5/8, 3/4, 7/8, 1”
ASA / ANSI SERIES				
SPROCKET PART #	SUITS CHAIN	TEETH / OD(mm)	BEARING SHAFT SIZES (mm)	BEARING SHAFT SIZES (inch)
IS-35A-15-35	35—3/8	15T— 50.6	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-40A-15-35	40—1/2	15T— 67.6	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-50A-15-35	50 – 5/8	15T— 83.0	10, 15, 16, 17	3/8, 1/2, 5/8, 3/4
IS-60A-15-47	60—3/4	15T— 101.5	17, 20, 25	5/8, 3/4, 7/8, 1”
IS-80A-13-47	80—1”	13T— 119.2	17, 20, 25	5/8, 3/4, 7/8, 1”
35mm OD BEARING SIZES—6003, 6202, 6300				
47mm OD BEARING SIZES—6005, 6204, 6303				