

UBC INCH BORE UC200 SERIES BEARINGS

PART NO	d inch	D mm	B mm	C mm	n mm	m mm	G mm	Load D-kN	Load S-kN	Max Rpm	Wgt kg
UC203-8	1/2	40	27.4	14	11.5	15.9	4.5	7.36	4.79	8000	0.12
UC203-9	9/16	40	27.4	14	11.5	15.9	4.5	7.36	4.79	8000	0.11
UC203-10	5/8										0.10
UC203-11	11/16	40	27.4	14	11.5	15.9	4.5	7.36	4.79	8000	0.10
UC204-8	1/2	47	31	17	12.7	18.3	5	12.81	6.65	6800	0.21
UC204-9	9/16	47	31	17	12.7	18.3	5	12.81	6.65	6800	0.19
UC204-10	5/8										
UC204-11	11/16	47	31	17	12.7	18.3	5	12.81	6.65	6800	0.19
UC204-12	3/4	47	31	17	12.7	18.3	5	12.81	6.65	6800	0.18
UC205-14	7/8	52	34.1	17	14.3	19.8	5	14.11	9.93	5700	0.22
UC205-15	15/16										0.20
UC205-16	1.00										0.19
UC206-17	1.1/16	62	38.1	19	15.9	22.2	5	19.49	11.31	4900	0.34
UC206-18	1.1/8										0.34
UC206-19	1.3/16										0.32
UC206-20	1.1/4										0.30
UC207-20	1.1/4	72	42.9	20	17.5	25.4	7	25.68	15.31	4100	0.52
UC207-21	1.5/16										0.48
UC207-22	1.3/8										0.48
UC207-23	1.7/16										0.46
UC208-24	1.1/2	80	49.2	21	19	30.2	8	29.12	17.84	3600	0.68
UC208-25	1.9/16										0.64
UC209-26	1.5/8	85	49.2	22	19	30.2	8	32.52	20.46	3400	0.78
UC209-27	1.11/16										0.74
UC209-28	1.3/4										0.70
UC210-30	1.7/8	90	51.6	24	19	32.6	10	35.05	23.18	3100	0.85
UC210-31	1.15/16										0.80
UC210-32	2.00										0.77
UC211-32	2.00	100	55.6	25	22.2	33.4	10	43.48	29.22	2800	1.22
UC211-34	2.1/8										1.10
UC211-35	2.3/16										1.05
UC212-36	2.1/4	110	65.1	27	25.4	39.7	10	52.52	32.93	2500	1.65
UC212-38	2.3/8										1.42
UC212-39	2.7/16										1.40
UC213-39	2.7/16	120	65.1	29	25.4	39.7	10	57.48	40.22	2400	1.96
UC213-40	2.1/2										1.94
UC214-43	2.11/16	125	74.6	30	30.2	44.4	12	62.11	45.03	2200	2.06
UC214-44	2.3/4										2.04
UC215-47	2.15/16	130	77.8	30	33.3	44.5	12	66.12	49.3	2100	2.30
UC215-48	3.00										2.13
UC217-52	3.1/4	150	85.7	35	34.1	51.6	12	83.24	63.89	1800	3.59
UC218-56	3.1/2	160	96	37	39.7	56.3	12	96.52	71.76	1700	4.56